

SL12-450

Compact passive trapezoidal 2-way loudspeaker with a 12" low frequency driver and a 1" high frequency compression driver on a 310W x 150H x 102D (mm), high frequency horn in an easily transportable trapezoidal enclosure.

Constructed from 18mm birch plywood, fitted with flush handles, pole mount socket, rubber feet, two Speakon NL4MP connectors and a 6mm punched powder coated steel grill.

Cloth covered version available on request

Features:

Passive 2-way full range
High frequency protection

Applications:

Live Sound
Mobile DJ
Fixed Installation

Actual size (H x W x D)

636mm X 396mm X 404mm

Weight: -



300 Watt version available, please call for more info.

Technical Specifications

Frequency Response: 55Hz - 18KHz (+/- 3dB)

LF Driver: 12"(305mm) / 3"(77mm) Voice Coil LF driver

HF Driver: 1"(25.4mm)Throat / 1.75"(44mm) Voice Coil HF compression unit

Impedance: 8 ohms

Average Sensitivity 1W/1M: 98dB

Power Handling: 450 Watts (AES), 900 Watts program

Maximum SPL Continuous/Peak: 121/127dB

Dispersion: 90°H x 40°V

Protective Grill: Black Perforated Steel

Soundlite Equipment, Unit 4, Providence Mill, Thornton Street,
Cleckheaton, West Yorkshire BD19 5BT

Tel: 01274 852032 E-mail info@soundlite.co.uk