

THE PROFESSIONAL SERIES SOVEREIGN PRO 12-300S

BASS DRIVER




12" / 304.8 mm CHASSIS DIAMETER	300 w (A.E.S.) POWER HANDLING	97.5 dB SENSITIVITY (1w / 1m)
45 Hz - 2.5 kHz FREQUENCY RESPONSE	2.5" / 63.5 mm COPPER - INSIDE / OUTSIDE WINDINGS VOICE COIL	Designed for use in 25-80 Litre ported enclosures

The Sovereign Pro 12-300S is intended for use in two-way ported enclosures, such as the classic bass driver plus horn tweeter or compression driver format. The unit features die cast chassis with long throw motor system and high linearity suspension allowing solid bass reproduction at high-power levels. The specially formulated cone pulp allows this driver to give a warm and smooth response throughout the bass frequency range and delivers well balanced tonal characteristics when properly matched to appropriate high-frequency drivers. The Sovereign Pro 12-300S is designed for use in 25 to 80 litre ported enclosures and features a 2.5 inch voice coil, 300 Watt power handling and 97.5 dB sensitivity.


- Highly versatile in 2-way ported enclosures.
- Optimised unit for warm coherent bass.
- Perfect for full range KTV systems.
- UK manufactured cone with optimised pulp offering increased strength, durability and performance.

THE PROFESSIONAL SERIES


FREQUENCY RESPONSE DATA*



IMPEDANCE



PREDICTED BASS RESPONSE



ELECTRO ACOUSTIC SPECIFICATIONS

Nominal Chassis Diameter	12" / 304.8 mm
Impedance	8 Ω
Power Handling	300 w (A.E.S.)
Peak Power (6dB Crest Factor)	1200 w (A.E.S.)
Usable Frequency Range -6dB	45 Hz - 2.5 kHz
Sensitivity (1 w - 1 m)	97.5 dB
Moving Mass inc. Air Load	60.68 grams
Minimum Impedance Zmin	6.84 Ω
Effective Piston Diameter	10.31" / 261.87 mm
Peak Displacement Volume of Cone Vd	0.27 litres
Magnet Weight	56 oz
Magnetic Gap Depth	0.31" / 7.87 mm
Flux Density	1.1 Tesla
Coil Winding Height	0.57" / 14.47 mm
Voice Coil Diameter	2.5" / 63.5 mm

MOUNTING / SHIPPING INFORMATION


Overall Diameter	13" / 330.2 mm
Width Across Flats	12.19" / 309.62 mm
Flange Height	0.305" / 7.8 mm
Baffle Hole Diameter F/M	11.03" / 280.16 mm
Baffle Hole Diameter R/M	10.13" / 257.30 mm
Gasket Supplied	Front & Rear
Fixing Holes	4x 0.218" diam on 12.5 PCD 4x 5.5 mm diam on 317.5 PCD
Depth	5.31" / 135 mm
Weight	10.25 lb / 4.65 kg
Recommended Enclosure Volume	0.88 - 2.83 cu ft / 25 - 80 litres
Shipping Weight	11.46 lb / 5.2 kg
Packing Carton Dimensions	165 x 330 x 330 mm

THIELE SMALL PARAMETERS

FS Hz	40 Hz
RE Ohms	5.5 Ω
Qms	11.68
Qes	0.33
Qts	0.32
Vas Ltr	101.26 litres
Vd litres	0.27 litres
CMS (mm/N)	0.256 mm/N
BL T/m	16.02 T/m
Mms (grams)	60.68 grams
Xmax (mm)	5.25 mm
Sd (cm²)	527.7 cm²
Efficiency %	2.10%
Le (1k Hz)	1.556 mH

MATERIALS OF CONSTRUCTION

Former Material	Kapton
Voice Coil	Copper - Inside / Outside Windings
Magnet Material	Ferrite
Chassis	Die-cast Aluminium
Cone	Curvilinear Paper
Surround / Edge Termination	Polyvinyl Damped Dbl. Half Roll Linen
Dust Dome	Solid Paper
Connectors	Push-button Spring Terminals
Polarity	Positive voltage at red terminal causes forward motion of cone



• Please enquire about alternative impedances.
 • A.E.S. power handling test. Pink noise bandpass filtered at 12 dB per octave with cutoff frequencies of 45 Hz and 450 Hz. Driver mounted in free air, test signal applied at rated power for two hours.
 • Please note that the frequency response measurements are supplied for comparison only and are not a measure of the low frequency performance which may be achieved in a fully optimised system.

SOVEREIGN PRO 12-300S

FANE