

SL15-600

Passive trapezoidal 2-way loudspeaker with a 15" low frequency driver and a 2" high frequency compression driver on a 450W x 250H x 230D (mm), high frequency horn in an a transportable trapezoidal enclosure.

Includes two stage high frequency protection system with massive L-pad heat sink to guard against HF driver overload.

Constructed from 18mm birch plywood, fitted with flush handles, pole mount socket, rubber feet, two Speakon NL4MP connectors and a 6mm punched powder coated steel grill. Both painted and cloth covered versions available on request.

Features:

Passive 2-way full range
High frequency protection

Applications:

Live Sound
Mobile DJ
Fixed Installation

Actual size (H x W x D)

779mm X 543mm X 482mm

Weight: 55kg



Light weight version available on request using neo drivers and 15mm birch plywood, if weight is a problem. please call for more info.

Technical Specifications

Frequency Response: 45Hz - 18KHz (+/- 3dB)

LF Driver: 15"(380mm) / 4"(122mm) Voice Coil LF driver

HF Driver: 2"(50.8mm)Throat / 2.87"(73mm) Voice Coil HF compression unit

Impedance: 8 ohms

Average Sensitivity 1W/1M: 99dB

Power Handling: 600 Watts (AES), 1200 Watts program

Maximum SPL Continuous/Peak: 123/129dB

Dispersion: 60°H x 75°V

Protective Grill: Black Perforated Steel

Soundlite Equipment, Unit 4, Providence Mill, Thornton Street,
Cleckheaton, West Yorkshire BD19 5BT

Tel: 01274 852032 E-mail info@soundlite.co.uk